



P.C.B LAYOUT

主要技术参数、性能

The Main Thchnology Performance

|   |                               |
|---|-------------------------------|
| 额定电流、电压<br>Rate voltage current         | DC 30V 0.1mA                  |
| 接触电阻<br>Contact resistance              | ≤100mΩ Max                    |
| 绝缘电阻<br>insulated resistance            | ≥100mΩ Min<br>DC 500V         |
| 耐受电压<br>Withstand Voltage               | AC500V 1Min                   |
| 电寿命<br>Electrical Life                  | 100,000 Cycles<br>above(Load) |
| 使用温度<br>Service temperature             | -25°C+ 80 °C                  |
| 使用湿度<br>Ambient humidity used           | ≤85%RH                        |
| 耐焊温度<br>Withstand Soldering temperature | 260°C ± 5°C<br>3S ± 1S        |

| E          |                   |                |           |                        |
|------------|-------------------|----------------|-----------|------------------------|
| D          |                   |                |           |                        |
| C          |                   |                |           |                        |
| B          |                   |                |           |                        |
| A          |                   |                |           |                        |
| 项目<br>ITEM | 名称<br>DESCRIPTION | 材质<br>MATERIAL | 数量<br>QYT | 表面处理/颜色<br>FINSH/COLOR |

|             |                 |                   |                |            | 第一视角<br>FIRST VIEW |                           |             | 名称/NAME:<br>按键开关<br>PUSH SWITCH SERIES |  |
|-------------|-----------------|-------------------|----------------|------------|--------------------|---------------------------|-------------|--|--|
|             |                 |                   |                |            |                    |                           |             | 型号/MODEL:<br>PG-2845C                  |  |
| 标记<br>SING  | 处数<br>FREQUENCY | 更改文件号<br>REVISION | 签名<br>APPROVED | 日期<br>DATE | 比列<br>SCALE        | 一般公差<br>GENERAL TOLERANCE |             |  |  |
| 设计 DESIGN   |                 | Zhaoming          |                |            | 单位<br>UNIT         | mm                        | 0.5~2       | ±0.10                                  |  |
| 审核 CHECKED  |                 | Zengyong          |                |            | 重量<br>WELGHT       |                           | 2~5         | ±0.15                                  |  |
| 批准 APPROVED |                 | Fuyunfeng         |                |            |                    |                           | 5~10        | ±0.20                                  |  |
|             |                 |                   |                |            |                    |                           | 角度<br>ANGLE | ±0.5°                                  |  |

