



PART NO	H	A	B	C
DS-015S-01	6.50±0.3	4.85max	5.15	6.05
DS-015S-02	8.00±0.3	6.35max	6.65	7.55

CIRCUIT DIAGRAM

主要技术参数、性能  
The Main Thchnology Performance

额定电流、电压 Rate voltage current	1mA 5VDC ~50 μ A 3V DC
接触电阻 Contact resistance	2Ω~5Ω. MAX
绝缘电阻 insulated resistance	100mΩ Min 100V DC
使用湿度 Ambient humidity used	≤85%RH
使用温度 Operating temperature	-25°C+80°C
耐焊温度 Withstand Soldering temperature	245°C±5°C 3S±0.5S
寿命 Life	100.000Cycles

项目 ITEM	名称 DESCRIPTION	材质 MATERIAL	数量 QYT	表面处理/颜色 FINISH/COLOR
E				
D				
C				
B				
A				

标记 SING	处数 FREQUENCY	更改文件号 REVISION	签名 APPROVED	日期 DATE	比列 SCALE	一般公差 GENERAL TOLERANCE	名称/NAME: 检测开关 DETECTOR SWITCH
设计 DESIGN		Zhaoming			单位 UNIT	0.5~2 ±0.10	型号/MODEL: DS-3450
审核 CHECKED		Zengyong			重量 WELGHT	2~5 ±0.15	
批准 APPROVED		Fuyunfeng				5~10 ±0.20	 三荣部品
						角度 ANGLE	

