



Model No.	DC00250	DC0025M
A	$\phi 8.0$	M8xP0.75

Model No.	DC0025M-A	DC0025M-B
	DC00250-A	DC00250-B
Schematic		

Model No.	DC00250- <u>H</u>	DC00250- <u>I</u>	DC00250- <u>J</u>
	DC0025M- <u>H</u>	DC0025M- <u>I</u>	DC0025M- <u>J</u>
PIN	$\phi 2.0$	$\phi 2.35$	$\phi 2.5$

主要技术参数、性能 The Main Thchnology Performance

额定电流、电压 Rate voltage current	DC 30V 0.5A
接触电阻 Contact resistance	$\leq 100m\Omega$
绝缘电阻 insulated resistance	$\geq 100m\Omega$ DC 500V
耐受电压 Withstand Voltage	AC 500V (50-60HZ)1min
电寿命 Electrical Life	5000 Cycles
使用温度 Service temperature	-25°C+ 80 °C
使用湿度 Ambient humidity used	$\leq 85\%RH$
耐焊温度 Withstand Soldering temperature	260°C \pm 5°C 5S \pm 1S

E				
D				
C				
B				
A				
项目 ITEM	名称 DESCRIPTION	材质 MATERIAL	数量 QYT	表面处理/颜色 FINSH/COLOR

						第一视角 FIRST VIEW		名称/NAME: DC插座 DC POWER JACK	
								型号/MODEL: DC025、DC025M	
标记 SING	处数 FREQUENCY	更改文件号 REVISION	签名 APPROVED	日期 DATE	比列 SCALE	一般公差 GENERAL TOLERANCE			
设计 DESIGN		Zhaoming			单位 UNIT	mm	0.5~2	± 0.10	
审核 CHECKED		Zengyong			重量 WELGHT		2~5	± 0.15	
批准 APPROVED		Fuyunfeng					5~10	± 0.20	
							角度 ANGLE	$\pm 0.5^\circ$	