



CIRCUIT DIAGRAM

Recommended PAD Layout ± 0.05
TOP VIEW

1. RATING:DC 15V,20mA Max DC 2V 10uA(min.)
2. OPERATING FORCE:160±50gf
3. TRAVEL:0.15mm±0.05
4. LIFE:300,000cycles
5. PACKAGE:5000Pcs/Reel

6	SHELL	1	PHOSPHOR BRONZE	Ag-Plate	东莞市三荣部品电子有限公司 DONGGUAN SAMYONG PARTS ELECTRONICS CO., LTD.												
5	FILM	1	PA	WHITE						TOLERANCES UNLESS OTHERWISE SPECIFIED		CLASS: <input type="checkbox"/> CONFIDENTIAL <input type="checkbox"/> SECRET <input checked="" type="checkbox"/> GENERAL					
4	KNOB	1	PA	BLACK	WITHIN: 1.5mm±0.1mm OVER: 1.5mm±0.2mm		NAME: TACT SWITCH										
3	CONTACT	3	SUS	Ag-Plate	APPD:		PART NO. TS-2416B										
2	TERMINAL	2	PHOSPHOR BRONZE	Ag-Plate	CHKD: FU XIAO FENG		<table border="1"> <tr> <td>UNIT</td> <td>SCALE</td> <td>SHEET</td> <td>UNIT</td> </tr> <tr> <td>mm</td> <td>1:1</td> <td>1/1</td> <td>B</td> </tr> </table>			UNIT	SCALE	SHEET	UNIT	mm	1:1	1/1	B
UNIT	SCALE	SHEET	UNIT														
mm	1:1	1/1	B														
1	CASE	1	PPA	BLACK	DR: ZENG YONG												
ITEM	PART NAME	Q'TY	MATERIAL	FINISH													